


## TECH BRIEF:

# SCHMERSAL INTERLOCK DEVICES FOR SATECH GUARDS

SCHMERSAL offers a wide range of compatible safety locks, safety sensors, and other accessories to complete the safety guarding solution. These devices have stock mounting brackets and accessories for use with SATECH guards.

**SATECH**  
Modular Machine Guards



### AZM300

- Electronic Solenoid Interlock
- RFID sensor, offers individual coding ("High" to ISO14119)
- 1,000 N Locking force
- Adjustable latching force 25/50N
- Symmetrical mounting for right- and left-hinged doors
- Can be used as end stop
- 3 actuating directions
- 3 LEDs signal operating status



### AZM201

- Electronic Solenoid Interlock
- RFID sensor, offers individual coding ("High" to ISO14119)
- 2,000 N Locking force
- Door handle actuator
- Optional inside emergency exit handle
- Actuator retracts into handle
- 3 LEDs signal operating status
- Lockout/tagout devices available



### BDF200

- Machine controls
- Housing matches AZM201
- Up to 4 control operations
- Control types:
  - E-Stop
  - Pushbutton
  - Illuminated pushbutton
  - Mushroom button
  - Signal light
  - Selector switch
  - Keyed selector
- Field customizable version



### RSS16

- Electronic Safety Sensor
- RFID sensor, offers individual coding ("High" to ISO14119)
- 3 actuating directions
- Optional magnetic latch
  - 40 N from front or back
  - 60 N from top
- Tolerates misalignments
- Optional M12 connector
- Serial Diagnostic version
- Wire in series without detriment to the safety level (to PLe)
- LEDs for status signaling



### SLC440

- Safety Light Curtain
- Multiple integrated functions:
  - blanking, double reset, contactor control
  - automatic mode, re-start mode, and beam coding
- Extruded aluminum housing, rectangular profile 28 x 33mm
- Protection heights from 170 to 1930 mm
- 14 or 30 mm resolutions for point of operation guarding
- 2, 3, or 4 beam grid for perimeter guarding
- LED signal endcaps
- Bluetooth interface



### SLC445

- Safety Light Curtain
- Muting function
  - Allows materials to pass in while not allowing workers
- Extruded aluminum housing, rectangular profile 28 x 33mm
- Protection heights from 170 to 1770 mm
- 14 or 30 mm resolutions for point of operation guarding
- 2, 3, or 4 beam grid for perimeter guarding
- LED signal endcaps

#### SCHMERSAL USA

15 Skyline Drive, Hawthorne, NY 10532  
Tel: 914-347-4775, Fax: 914-347-1567  
E-mail: salesusa@schmersal.com  
www.schmersalusa.com

#### SCHMERSAL CANADA

29 Centennial Road, Unit 1, Orangeville ON L9W 1R1  
Tel: 519-307-7540, Fax: 519-307-7543  
E-Mail: salescanada@schmersal.com  
www.schmersalcanada.ca



**SCHMERSAL**  
THE DNA OF SAFETY