


TECH BRIEF:

SCHMERSAL INTERLOCK DEVICES FOR SATECH GUARDS

SCHMERSAL offers a wide range of compatible safety locks, safety sensors, and other accessories to complete the safety guarding solution. These devices have stock mounting brackets and accessories for use with SATECH guards.

SATECH
Modular Machine Guards



AZM300

- Electronic Solenoid Interlock
- RFID sensor, offers individual coding ("High" to ISO14119)
- 1,000 N Locking force
- Adjustable latching force 25/50N
- Symmetrical mounting for right- and left-hinged doors
- Can be used as end stop
- 3 actuating directions
- 3 LEDs signal operating status



AZM201

- Electronic Solenoid Interlock
- RFID sensor, offers individual coding ("High" to ISO14119)
- 2,000 N Locking force
- Door handle actuator
- Optional inside emergency exit handle
- Actuator retracts into handle
- 3 LEDs signal operating status
- Lockout/tagout devices available



BDF200

- Machine controls
- Housing matches AZM201
- Up to 4 control operations
- Control types:
 - E-Stop
 - Pushbutton
 - Illuminated pushbutton
 - Mushroom button
 - Signal light
 - Selector switch
 - Keyed selector
- Field customizable version



RSS16

- Electronic Safety Sensor
- RFID sensor, offers individual coding ("High" to ISO14119)
- 3 actuating directions
- Optional magnetic latch
 - 40 N from front or back
 - 60 N from top
- Tolerates misalignments
- Optional M12 connector
- Serial Diagnostic version
- Wire in series without detriment to the safety level (to PLe)
- LEDs for status signaling



SLC440

- Safety Light Curtain
- Multiple integrated functions:
 - blanking, double reset, contactor control
 - automatic mode, re-start mode, and beam coding
- Extruded aluminum housing, rectangular profile 28 x 33mm
- Protection heights from 170 to 1930 mm
- 14 or 30 mm resolutions for point of operation guarding
- 2, 3, or 4 beam grid for perimeter guarding
- LED signal endcaps
- Bluetooth interface



SLC445

- Safety Light Curtain
- Muting function
 - Allows materials to pass in while not allowing workers
- Extruded aluminum housing, rectangular profile 28 x 33mm
- Protection heights from 170 to 1770 mm
- 14 or 30 mm resolutions for point of operation guarding
- 2, 3, or 4 beam grid for perimeter guarding
- LED signal endcaps

SCHMERSAL USA

115 E Stevens Avenue, Suite 208, Valhalla, NY 10595
Tel: 914-347-4775, Fax: 914-347-1567
E-mail: salesusa@schmersal.com
www.schmersalusa.com

SCHMERSAL CANADA

29 Centennial Road, Unit 1, Orangeville ON L9W 1R1
Tel: 519-307-7540, Fax: 519-307-7543
E-Mail: salescanada@schmersal.com
www.schmersalcanada.ca



SCHMERSAL
THE DNA OF SAFETY